

**NOTES:**

1. SIGN SHEETING FOR ALL SIGNS SHALL BE DIAMOND GRADE. SIGN THICKNESS SHALL BE .080 GAUGE MINIMUM. ALL MATERIALS & SIZES SHALL BE IN CONFORMANCE WITH THE LATEST EDITION OF THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD). COUNTY SPECIFICATIONS & DIMENSIONS SHALL PREVAIL WHEN THEY EXCEED THE MINIMUM AS REQUIRED BY THE M.U.T.C.D.
2. SIGNS SHALL BE MOUNTED WITH VANDAL-PROOF HARDWARE.
3. ON STREETS WHERE CURB DOES NOT EXIST, SET EDGE OF SIGN CLOSEST TO ROADWAY AT A MINIMUM OF 6 FEET FROM PAVEMENT EDGE.
4. 7'-0" MINIMUM DIMENSION IS MEASURED FROM FINISHED GRADE AT POST LOCATION WHERE CURB EXISTS, OR FROM FINISHED PAVEMENT SHOULDER WHERE NO CURB EXISTS.

<b>DATE</b>	<b>REVISIONS</b>		<b>STANDARD DETAILS FOR PUBLIC WORKS CONSTRUCTION</b>  <b>STANDARD TRAFFIC SIGN</b> <b>NOTES</b>	<b>SECTION NUMBER:</b> <b>400</b>
			<b>DRAWING NUMBER:</b> <b>W-402C</b>	
			<b>DATE:</b> <b>2/21/2022</b>	